



Moisture measuring instrument MFM 22



Benefits

- TÜV-approval as per VDI 4206-4. First TÜV-tested standalone wood moisture measuring instrument as per 1st German Federal Immission Act
- With characteristics for 400 wood types and 28 construction materials stored in the software – no complex conversion tables for construction material required
- Ready in no time: Assignment of favourites "Sort" with frequently measured firewood types and wood chips as per 1st German Federal Immission Act
- Menu-guided three-point mean value measurement for split logs
- Auto-hold function: Fully automatic for determination of an accurate measured value in the case of electrostatic charge (e.g. dry wood)
- Visual range alarm: The characteristic flashes if the u value is < 8 % or > 40 %
- Special electrode with temperature probe TÜV-tested according to test report M 1167-01/15 as per VDI 4206-4 for wood chips and pellets
- Insertion probe for wood chips and pellets with improved ergonomics and optimised cable routing for superior handling
- Versatile application due to special probes for pellets, wood chips, log wood, screed, plaster, concrete, brickwork, paper, etc.



Application

For precise and standards-compliant evaluation of the residual moisture content and the temperature of pellets and wood. The integrated three-point mean value function (measured value as a result of the mean value of measurements at three reference points of the split log) also complies with the requirements of the 1st German Federal Immission Act. MFM 22 is also suitable for measurements of moisture in buildings (e.g. plaster, concrete, screed). Water content and material moisture are determined by means of a resistance method directly at the sample. The correct measured value is calculated on the basis of material-specific characteristics. The integrated temperature compensation is an essential feature in obtaining correct measurements at wood fuels and the corresponding wood chips or pellets. MFM 22 is the ideal general purpose measuring instrument for residual moisture.

Versions

	Part no.
Moisture measuring instrument MFM 22	569087
Moisture measuring instrument MFM 22 set 1 incl. hammer electrode HLH-HE 22 with TÜV approval, for MFM 22	P569087-1
Moisture measuring instrument MFM 22 set 2 incl. ram electrode ELE-SE 10, for MFM 22	P569087-2

Blue part no. = in-stock items



Technical specifications

Measuring range

Moisture u: 0/100 %
 Temperature: -40/+200 °C

Resolution

Moisture u: 0.1 %
 Temperature: 0.1 °C

Accuracy

Moisture u: $\pm 0.2 \%$
 Temperature: $\pm 0.3 \text{ K} \pm 0.5 \% \text{ v. Mw.}$

Operating temperature range

Ambient: -25/+50 °C
 Storage: -25/+70 °C

Weight

Approx. 175 g

Dimensions

W x H x D: 71 x 142 x 26 mm

Display

LCD
 W x H: 38 x 25 mm

Supply voltage

1 x 9 V monobloc battery

Approval

TÜV approval as per VDI 4206-4

Scope of delivery

- MFM 22:
 - Measuring instrument MFM 22
 - 9 battery
- MFM 22 set 1:
 - Measuring instrument MFM 22
 - 9 battery
 - Measuring cable 1 m with connector
 - Steel pins 40 mm
 - Case
 - Hammer electrode ELE-HE 20 with TÜV approval
- MFM 22 set 2:
 - Measuring instrument MFM 22
 - 9 battery
 - Measuring cable 1 m with connector
 - Steel pins 40 mm
 - Case
 - Ram electrode ELE-SE 10