



Flue gas analyser EUROLYZER® S1 set Pro



Benefits

- Large high-resolution display for optimum readability and intuitive menu navigation, protected by scratch-resistant glass
- Pioneering "dual-mode concept": Intuitive one-hand operation via scroll wheel or touch display – sensitive even with work gloves
- Ready for all typical HVAC measuring tasks thanks to Bluetooth® connection to more than 35 sensor modules and sets of the CAPBs® system
- TÜV-tested measurement as per 1st and 44th BImSchV (German Federal Immission Act)
- NO sensor can be retrofitted
- H₂-compensated robust CO sensor (measuring range up to 10,000 ppm)
- Configurable macros for repetitive tasks
- Multi-memory: Combine up to six different measurements into a single measurement report (for example, full load measurement/partial load measurement or flue gas measurement and flow pressure measurement)
- Data transmission via Bluetooth® or QR code to the AFRISO app EuroSoft® connect for on-site documentation
- 5 years warranty on O₂ sensor
- 7 years full warranty in connection with a service contract



Application

Designed for flue gas measurements at oil, gas and pellets fired systems as well as for tightness tests at gas lines, for checking the connection pressure/flow pressure and the pressure loss. TÜV-tested measurements as per 1st and 44th BImSchV (German Federal Immission Act) can be performed reliably and intuitively. Fast and easy Bluetooth® connection to more than 35 sensor modules and sets of the AFRISO CAPBs® make EUROLYZER® S1 the central controller for all HVAC tasks.

Versions

	Part no.
Flue gas analyser EUROLYZER® S1 set Pro O ₂ , CO/H ₂ +, draft, pressure	P00141

Blue part no. = in-stock items



Technical specifications

Measuring ranges (measured values)

Flue gas temperature/differential temperature
0/1,150 °C

Air temperature/combustion air temperature
-20/+200 °C

Draft
-70/+70 hPa

Differential pressure
-150/+150 hPa

O₂ measurement
0/21 Vol.-%

CO₂ measurement
Nominal: 0/4,000 ppm
Maximum: 0/10,000 ppm

Additional technical specifications

Indication (calculated values)
CO₂, CO_{Undiluted (air-free)}, Lambda, Dew point, Eta efficiency, Flue gas losses q_A, CO mg/m³ (natural gas), CO mg/kWh (fuel oil)

Operating temperature range
Ambient: 0/40 °C
Storage: -20/+50 °C

Weight (measuring instrument)
500 g

Dimensions
W x H x D: 80 x 218 x 44 mm

Degree of protection
IP 42 (EN 60529)

Display
High-resolution display 4.3 "

Connections

Draft: Ø 7 mm
Pressure: Ø 8 mm
Gas: Ø 8 mm
Temperature: 2 x socket type K

Supply voltage

Lithium-ion battery (3.6 V/5,000 mAh)
Power supply unit (USB-C)
Battery or mains

Hours of operation (eco mode)
12 Stunden

Data memory

Internal memory, 10,000 Messungen

Interfaces

Infrared,
Bluetooth®,
QR code generator,
USB-C

Approvals

TÜV-tested as per 1st and 44th BImSchV,
DIN EN 50379-1/2

Scope of delivery

- With integrated magnet in housing
- Calibration report
- Quick charge power supply unit NTE 5 SF
- Charging cable USB-A to USB-C (1 m)
- 5 x Infiltec fine filter
- 5 x Teflon membrane
- Condensate filter cartridge KFP
- Base handle AWS-B for interchangeable probes
- Interchangeable probe AWS-S 180 mm
- Ambient air probe TFB-UL 50-1
- Hose for gas connection pressure
- Hard top case Pro blue